



garland  
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


## Part No: MJ3000

Description	22AWG Stranded TACW, Twisted Pairs, Foam PE Insulation, Al. Foil Overall Screen, 22AWG TACW Drain Wire, 65% TACW Braiding, PVC Sheath.
Applicable Standards	AS/NZS 1125, AS 1049
Suitable Applications	Suitable for data transmission and control applications using EIA RS-485. May be used for RS-485 based DMX lighting control. *Not intended for direct connection to mains power.

### Cable Construction Drawing



### Cable Construction Relative Parts



### Cable Description

Conductor	AWG	Area(mm²)	Stranding	Diameter(mm)	Material
	22	0.34	7/0.25	0.75	TACW
Insulation	Pairs :		1		
	Material :		Foam PE		
	Colour :		White/Blue		
	Nominal Thickness (mm) :		0.6		
	Nominal OD (mm) :		2.1		
Screen	Material : Al. Foil		Coverage: 100%		

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99  
www.garlandcables.com.au

MJ3001-200109

made by





Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Drain Wire	AWG	Area(mm <sup>2</sup> )	Stranding	Diameter(mm)	Material
	22	0.34	7/0.25	0.75	TACW
Braiding	Material : TACW Coverage : 65%				
Sheath	Material :		UV-PVC		
	Colour :		Black		
	Nominal Thickness (mm) :		1.0		
	Nominal OD (mm) :		7.1		

### Electrical Properties

Rated Voltage	300V
Max. Conductor DC Resistance @ 20°C	55.0 $\Omega$ /km
Characteristic Impedance	120 $\pm$ 15 $\Omega$
Nom. Capac. Conductor to Cond.	50pF/m
Voltage Test: Core to Core	1.5kV dc/1min
Voltage Test: Core to Shield	1.5kV dc/1min

### Mechanical Properties

Operating Temperature Range	-15 to 80°C
Max. Recommended Pulling Tension	48N
Min. Bend Radius (install)	71mm
Approximate Mass	6.2kg/100m

### Supply Information

Part Number	Pack Size	Pack Type	Dimensions	Qty Per Carton
MJ3000BK305	305m	Wooden Reel	W40 x H21.8cm	1R

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99  
[www.garlandcables.com.au](http://www.garlandcables.com.au)

MJ3001-200109

