



garland
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


Part No: MJ9002

Description	24AWG Stranded TACW, 2 Twisted Pairs, Foam PE Insulation, Al. Foil Overall Screen, 24AWG TACW Drain Wire, 90% TACW Braiding, PVC Sheath.
Applicable Standards	AS/NZS 1125, AS 1049
Suitable Applications	Suitable for data transmission and control applications using EIA RS-485. May be used for RS-485 based DMX lighting control. *Not intended for direct connection to mains power.

Cable Construction Drawing



Cable Construction Relative Parts



Cable Description

Conductor	AWG	Area(mm²)	Stranding	Diameter(mm)	Material
	24	0.22	7/0.203	0.61	TACW
Insulation	Pairs :		2		
	Material :		Foam PE		
	Colour :		White/Blue, White/Orange		
	Nominal Thickness (mm) :		0.58		
	Nominal OD (mm) :		1.77		
Screen	Material : Al. Foil		Coverage: 100%		

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.garlandcables.com.au

MJ9002-200109

made by





Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Drain Wire	AWG	Area(mm ²)	Stranding	Diameter(mm)	Material
	24	0.22	7/0.203	0.61	TACW
Braiding	Material : TACW Coverage : 90%				
Sheath	Material :		PVC		
	Colour :		Grey		
	Nominal Thickness (mm) :		1.2		
	Nominal OD (mm) :		8.5		

Electrical Properties

Rated Voltage	300V
Max. Conductor DC Resistance @ 20°C	89.0 Ω /km
Characteristic Impedance	120 \pm 15 Ω
Nom. Capac. Conductor to Cond.	50pF/m
Voltage Test: Core to Core	1.5kV dc/1min
Voltage Test: Core to Shield	1.5kV dc/1min

Mechanical Properties

Operating Temperature Range	-15 to 80°C
Max. Recommended Pulling Tension	63N
Min. Bend Radius (install)	85mm
Approximate Mass	8.6kg/100m
Sheath Printing	TBA

Supply Information

Part Number	Pack Size	Pack Type	Dimensions	Cartons Per Pallet
MJ9002GY305	305m	Wooden Reel	W44 x H21.8cm	TBA

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.garlandcables.com.au

MJ9002-200109

